

CPE10040 Outdoor

Specifications

Band Frequency	LTE B40 only: 2300MHz~2400MHz
LTE	3GPP Release 9
LTE UE Category	4
MIMO	4x2
Band Width	5/10/15/20 MHz
USIM	3.3V or 1.8V Push-push socket
Configuration	Web GUI
Management	USIM Management LTE System Information Display Firmware Upgrade through HTTP



3GPP Ready - Release 9



Water and Dust Proof



Antenna 1Tx / 2RX



Web GUI

Features

Dimensions (HxWxD)	195(L)*187(W)*78(H) mm
RF Transmit Power	23dBm
Antenna	10dBi
Power Supply	PoE
Power Consumption	8W
Maximum Transmit Power	23dBm
USIM	3.3V or 1.8V Push-push socket
LAN	1 x RJ45 Port with PoE Pin
Temperature	Operation -30° to 60° C Storage -35° to 80° C
Operation Humidity	5% ~95%

Get More from Wireless. Contact Telrad today www.telrad.com 1-844-4TEL RAD

CPE10040 Indoor

Specifications

Wi-Fi	802.11b/g/n
Configuration	Firmware Upgrade through HTTP TR069
Security	AES, WPA,WPA2 64bits WEP, 128bits WEP
WLAN	Up to 32 users
Interface	Power Switch 3x100M RJ45 Reset Key WPS
RF Transmit Power	802.11b: 18± 1.5 dBm 802.11g: 17 ± 1.5 dBm 802.11n: 16 ± 1.5 dBm
Receive Sensitive	802.11b: -83dBm 802.11g: -70dBm 802.11n: -64dBm
Receive Sensitive	2 WiFi Antennas



PoE - Passive PoE



WEP,WPA,WPA2, AES, TKIP



802.11b/g/n



Web GUI - Esier Configuration

Features

Dimensions (HxWxD)	180(L)*128(W)*23(H) mm
Operation Temperature	0~40° C
Storage Temperature	-30~80° ° C
Operation Humidity	5% ~95%
Power Supply	12V
PoE	For ODU

Get More from Wireless. Contact Telrad today www.telrad.com 1-844-4TEL RAD